Apparatus And Method Of Direct Mode Radio Communication

Technical Field

The invention relates to apparatus and method of direct
5   mode radio communication. In particular, it relates to
group calls and other services for direct mode radio
communication.

Background

10   Digital voice and data communications that use Radio
Frequencies (RF) as their transmission medium are
conventionally classified into Private Mobile Radio (PMR)
or Specialized Mobile Radio (SMR) technologies.

15   All the various implementations that evolved from these
fundamental technologies are modelled around a network of
static, interconnected ("Trunked") radio communication
nodes, collectively known as a trunked radio network. This
network is responsible for efficiently controlling and
20   managing the available medium resources, specifically RF
spectra and time division multiple access (TDMA)
multiplexing, in order to maximise resource utilization,
reliability and consistency.

25   Moreover, the network is responsible for synchronizing the
various radio terminals (mobile stations, or MS) both in
terms of frequency and timing, to allocate the medium
resources to each MS individually and to funnel all the
signals between MSs through the network paths.
30
In order to supplement this primary model in cases where
access to the trunked network system is not available (for
example due to range, capacity or operational
considerations) a complementary communication model was
35   developed, namely, the "Direct" radio link. As opposed to
the trunked radio network, the direct radio link relegates

the controlling duties of the trunked system to the MS
initiating the direct radio link.

However, unsurprisingly not all the facilities that a
central trunked system is capable of providing in a trunked
mode of operation (TMO) can easily be replicated in the
supplementary direct mode of operation (DMO), even if these
facilities are highly desirable.

The purpose of the present invention is to provide one such
facility in direct mode operation, namely a DMO talk group
scan functionality.

Summary of the Invention
In a first aspect, the present invention provides a method
of direct mode radio communication, as claimed in claim 1.

In a second aspect, the present invention provides a mobile
station, as claimed in claim 17.

Further features of the present invention are as defined in
the dependent claims.

Embodiments of the present invention will now be described
by way of example with reference to the accompanying
drawings, in which:

Brief description of the drawings
FIG. 1 is a schematic diagram depicting mobile stations
belonging to one or more of three user groups, in
accordance with an embodiment of the present invention.

FIG. 2 is a schematic diagram depicting mobile stations bellowing to one or more of three user groups, and wherein a first mobile station initiates a call, in accordance with an embodiment of the present invention.

FIG. 3 is a schematic diagram depicting mobile stations bellowing to one or more of three user groups, and wherein a second mobile station initiates a call, in accordance with an embodiment of the present invention.

Detailed description

A method of DMO service scanning is disclosed. This method is not limited to any particular PMR or SMR device, but for the sake of clarity the following description is given with reference to the ETSI TErrestrial Trunked RAdio (TETRA) standard (see www.etsi.org).

According to the current TETRA standard, a TETRA MS operating in direct mode monitors its channel for activity relating to the user group to which it belongs (e.g. a set of one or more associated MSs which share the same group address).

In particular, a TETRA MS operating in Direct Mode on a selected RF channel, and while having no knowledge of the selected channel's state, continuously monitors this channel for any TETRA specific RF activity.

Once any TETRA specific RF activity is detected, the MS synchronizes with the first fully decoded TETRA direct mode synchronization burst (DSB). If this synchronization burst is addressed to the group that the MS (110, 120, 130) is

currently set to receive any calls or other TETRA services from, it joins the call or responds to the service.

Similarly, a TETRA MS that initiates a call or another TETRA service does so acting as a DMO master MS on its RF channel.

Thus in both DMO monitoring and DMO master roles, an MS abiding by the TETRA standard only addresses one channel and is consequently ignorant of any other TETRA activity that might be taking place on another RF channel, and which may be of interest to the user of the MS.

An example scenario is where a middle manager at a work site or a middle ranking officer in the armed forces typically has a role of relaying instructions down the chain of command;

If they have initiated a call to a group in order to relay instructions to their staff, then the manager or officer could not become aware of a higher-ranking manager or commander initiating a call to a group of middle ranking staff to which they belong being conducted at the same time, but which typically they would rather join.

In short, the current DMO communication methodology can break a chain of information or command because a DMO mobile handset will monitor and connect only over one channel at a time, and does not monitor activity from other channels whilst monitoring a specific one.

The present invention provides a method of multi channel scanning in direct mode operation. Such multi channel

scanning enables, inter alia, a method of adapting the
trunked feature 'talk group scan' (TGS) to direct mode
operation.

In essence, TMO TGS monitors channel activity in the
5   networked system and enables detectability and selection of
other groups on other channels by an MS.

A novel method of DMO multi-channel scanning is now
described below for a TETRA system in a DMO TGS scenario;
10   the current TETRA DMO protocols, procedures and conventions
described in the standard (see ETS 300 396-3 at
http://www.etsi.org) are observed.

Referring to Figure 1, in an embodiment of the present
15   invention, a plurality of MSs 110 is depicted arranged in a
number of groups indicated as Group A, Group B and Group C.
Each MS 110 maintains at least a first selectable DMO group
set (DGS) to choose from, where a DGS comprises a list of
groups and their respective direct mode RF channel.
20   Selection may be automatic or by the user.

It is assumed that all the MSs 110 party to the various
groups for a given scenario will use the same DGS.

25   Each group in a DGS is assigned a unique sequence number
(USN) related to their position in the list.

An MS 110 conducts a channel surveillance procedure for
those RF channels associated with the groups in the
30   selected DGS whose channel state is free/unknown.

The TETRA DMO standard ETS 300 396-3, section 8.4.2.2.1
states:

A DM-MS which has just been switched into
direct mode operation or following initial power
up in direct mode shall conduct continuous
monitoring of the selected DM radio frequency
carrier in order to detect any DSBs (direct mode
synchronization bursts) present and decode any
layer 2 information available.

Continuous monitoring of the DM radio
frequency carrier means that a DM-MS shall sample
the DM radio frequency carrier at a sufficient
rate so that the presence of a DSB may be
determined.

A DM-MS shall conduct the procedure to
determine the initial state of the DM radio
frequency carrier over a period of at least 19
frame durations or until DSBs are detected.

In an embodiment of the present invention, rather than the
single selected channel described in the TETRA DMO standard
passage above, the surveillance procedure steps though the
RF channels associated with the groups periodically, to
determine if there is any RF activity. Any order of
stepping through the RF channels is acceptable. For
example, one such procedure involves taking five one-
millisecond samples on consecutive group RF channels per
frame.

By interleaving samplings of the RF channels in this
manner, all the group channels are monitored essentially
simultaneously until either at least a period of 19 frames
(approximately 1 second) has elapsed or one or more DSBs
are detected.

It will be clear to a person skilled in the art that in principle the surveillance procedure may continue indefinitely.

Referring now to Fig. 2, if there is currently no group
5   activity on any of the surveyed channels, then the first TETRA call or service to start on any of the groups determines the physical and logical time division pattern (TDP) for all surveyed channels. An MS initiating such a call is called a master MS, depicted in Fig. 2 as MS 220.
10   In the case of Fig 2, an MS 220 of a mid-ranking manager that is a member of two groups is depicted initiating a call to one of these groups.

The other TETRA MSs 110 detecting this activity, whether a
15   member of the addressed group or more generally a member of the DGS, synchronise to this timing regime, adopting the same frame and slot numbering as the Master MS 220. ·

Having found a TETRA call or service from among the groups
20   of the selected DGS, a second group channel survey mode is now employed:

An embodiment of the present invention exploits currently unassigned time slots available during a call or service,
25   for example in TETRA time slot #3 on each of the Request Bit Map associated frames 1, 4, 7, 9, 10, 13, 15 and 16 (see ETS 300 396-3 sections 8.4.7.9 and 9.6.13).

Each Master MS 220 currently making a call will transmit a
30   presence signal burst on a specific time slot in such a frame on its own RF channel, the specific frame being assigned according to the corresponding group position in the DGS. Thus for example, a Master MS 220 transmitting to

a third group in a DGS will use a time slot in frame 7, whilst an MS transmitting to a seventh group in the DGS will use a time slot in frame 15. Any relationship that uniquely maps DGS group position to a specific time-slot is acceptable.

Typically, each slave or idle MS 110 (a slave MS is party to a call, while an idle MS is not) shall listen during these time slots to the relevant channel for a presence signal indicating activity in an alternative group.

Clearly, a Master MS 220 may also listen to the time slots of other groups than its own in a similar manner.

This method is referred to as the DMO Coupled Control Channel (DCCC).

In an alternative embodiment, a specific RF channel is assigned on which all Master MSs 220 transmit their presence signal bursts at the relevant times and to which all MSs listen at the relevant times. This method is referred to as the DMO Alternative Control Channel (DACC).

In both the DCCC and DACC cases, the first TETRA Master MS 220 signals all call or service recipients that the request bit map associated time slots are not available for random access requests (see ETS 300 396-3 section 9.6.13), leaving them reserved for the DCCC and DACC schemes described above.

Table 1 overleaf illustrates an example time division pattern for the DMO Coupled Control Channel method, for a DGS containing groups A-H:

Fr 1	Fn 2	Fn 3	Fn 4	Fn 5	Fn 6	Fn 7	Fn 8	Fn 9	Fn 10	Fn 11	Fn 12	Fn 13	Fn 14	Fn 15	Fn 16	Fn 17	Fn 18	RF channel A
Fn 1	Fn 2	Fn 3	Fn 4	Fn 5	Fn 6	Fn 7	Fn 8	Fn 9	Fn 10	Fn 11	Fn 12	Fn 13	Fn 14	Fn 15	Fn 16	Fn 17	Fn 18	RF channel B
Fn 1	Fn 2	Fn 3	Fn 4	Fn 5	Fn 6	Fn 7	Fn 8	Fn 9	Fn 10	Fn 11	Fn 12	Fn 13	Fn 14	Fn 15	Fn 16	Fn 17	Fn 18	RF channel C
Fn 1	Fn 2	Fn 3	Fn 4	Fn 5	Fn 6	Fn 7	Fn 8	Fn 9	Fn 10	Fn 11	Fn 12	Fn 13	Fn 14	Fn 15	Fn 16	Fn 17	Fn 18	RF channel D
Fn 1	Fn 2	Fn 3	Fn 4	Fn 5	Fn 6	Fn 7	Fn 8	Fn 9	Fn 10	Fn 11	Fn 12	Fn 13	Fn 14	Fn 15	Fn 16	Fn 17	Fn 18	RF channel E
Fn 1	Fn 2	Fn 3	Fn 4	Fn 5	Fn 6	Fn 7	Fn 8	Fn 9	Fn 10	Fn 11	Fn 12	Fn 13	Fn 14	Fn 15	Fn 16	Fn 17	Fn 18	RF channel F
Fn 1	Fn 2	Fn 3	Fn 4	Fn 5	Fn 6	Fn 7	Fn 8	Fn 9	Fn 10	Fn 11	Fn 12	Fn 13	Fn 14	Fn 15	Fn 16	Fn 17	Fn 18	RF channel G
Fn 1	Fn 2	Fn 3	Fn 4	Fn 5	Fn 6	Fn 7	Fn 8	Fn 9	Fn 10	Fn 11	Fn 12	Fn 13	Fn 14	Fn 15	Fn 16	Fn 17	Fn 18	RF channel H

Table 1. Example TDP for DCCC method.

Table 2 below illustrates an example time division pattern for the DMO Alternative Control Channel method, for a DGS containing groups A-H:

*	Fn 2	Fn 3	Fn 4	Fn 5	Fn 6	Fn 7	Fn 8	Fn 9	Fn 10	Fn 11	Fn 12	Fn 13	Fn 14	Fn 15	Fn 16	Fn 17	Fn 18	RF channel A
Fn 1	Fn 2	Fn 3	*	Fn 5	Fn 6	Fn 7	Fn 8	Fn 9	Fn 10	Fn 11	Fn 12	Fn 13	Fn 14	Fn 15	Fn 16	Fn 17	Fn 18	RF channel B
Fn 1	Fn 2	Fn 3	Fn 4	Fn 5	Fn 6	*	Fn 8	Fn 9	Fn 10	Fn 11	Fn 12	Fn 13	Fn 14	Fn 15	Fn 16	Fn 17	Fn 18	RF channel C
Fn 1	Fn 2	Fn 3	Fn 4	Fn 5	Fn 6	Fn 7	Fn 8	*	Fn 10	Fn 11	Fn 12	Fn 13	Fn 14	Fn 15	Fn 16	Fn 17	Fn 18	RF channel D
Fn 1	Fn 2	Fn 3	Fn 4	Fn 5	Fn 6	Fn 7	Fn 8	Fn 9	*	Fn 11	Fn 12	Fn 13	Fn 14	Fn 15	Fn 16	Fn 17	Fn 18	RF channel E
Fn 1	Fn 2	Fn 3	Fn 4	Fn 5	Fn 6	Fn 7	Fn 8	Fn 9	Fn 10	Fn 11	Fn 12	*	Fn 14	Fn 15	Fn 16	Fn 17	Fn 18	RF channel F
Fn 1	Fn 2	Fn 3	Fn 4	Fn 5	Fn 6	Fn 7	Fn 8	Fn 9	Fn 10	Fn 11	Fn 12	Fn 13	Fn 14	*	Fn 16	Fn 17	Fn 18	RF channel G
Fn 1	Fn 2	Fn 3	Fn 4	Fn 5	Fn 6	Fn 7	Fn 8	Fn 9	Fn 10	Fn 11	Fn 12	Fn 13	Fn 14	Fn 15	*	Fn 17	Fn 18	RF channel H

Fn 1	Fn 2	Fn 3	Fn 4	Fn 5	Fn 6	Fn 7	Fn 8	Fn 9	Fn 10	Fn 11	Fn 12	Fn 13	Fn 14	Fn 15	Fn 16	Fn 17	Fn 18	Alternative channel

Table 2. Example TDP for DACC method.

In tables 1 and 2 above, frames 6, 12, and 18 are used by
the master MSs for synchronisation, as per the TETRA
5   standard.

If a DGS in a TETRA system comprises more than 8 groups,
other time slots may be utilised (for example, time slot 3
of frames 2, 5, 8, 11, 14 and 17 above, normally reserved
10   for slave or idle but occupied MSs, and wherein any clashes
that may occur from the slave or idle MSs perspective are
recoverable by retransmission processes within the
standard).

15   Referring finally to Fig. 3, an MS 330 of a high-ranking
manager is depicted initiating a call or service to a group
comprising the mid-ranking manager's MS 220, but different
to that group to which the mid-ranking manager's MS 220
itself is making a call.
20
When an additional active group is detected, the MS (110,
220) may alert the user to the activity. However, a number
of strategies are possible in this regard. For example,
groups within the DGS may be assigned a rank, so that
25   activity on a high ranking group results in automatic
switching from lower ranking calls to that group (in
accordance with the prevailing standard procedures), or in
prioritising channel activity information to the user.

30   In a similar vein, individual master MSs corresponding to
key personnel, identified via their presence signal burst,

may be ranked in a similar manner for switching or
information purposes.

Finally, not all MSs may be granted access to all groups in
5   the DGS, and so not alert their users to activities in
these groups. Indeed, in an alternative embodiment of the
present invention, an MS (110, 220) will only monitor those
time slots in the DCCC and DACC schemes relevant to groups
that they are entitled to join.
10

In the scenario of Fig.3, therefore, the mid-ranking
manager may be made aware of the high-ranking manager's
call, and may wish to end his or her own call to join. Thus
the chain of information or command can be maintained in
15   direct mode operation in this scenario.

In the event of an undesired presence signal burst (i.e. an
unexpected target address in a specific time slot) for
example caused by an MS coming within range that does not
20   share the common DGS, then a TETRA MS (110, 220, 330) shall
activate an appropriate counter to time out the undesired
call/service. Similarly, if unexpected messages are decoded
or not messages are received when expected (e.g due to
cyclic redundancy check, or CRC errors), other counters
25   shall be started to time out the service. All other DMO
timers and counters are retained and handles as per the
TETRA DMO standard.

It will be understood that the method of direct mode radio
30   communication as described above, provides at least one or
more of the following advantages in direct mode operation:

i. MSs are able to scan multiple channels when there are currently no group calls or services;

ii. MSs are able to scan multiple channels when there are currently one or more group calls or services;

iii. MSs can inform the user about calls or services occurring on other channels, or automatically switch to more important calls or services.

iv. Chains of information or command are not necessarily broken by ignorance of other channel activity.